

Power Units Comparison Chart

Motor Type	Model No.	Use For	Power Rqmt.	Max Pressure (psi)	Oil Delivery (Cubic In./Min)		Motor Size (HP)	Reservoir Capacity (Gallons)	Dimensions (Inches)				Valve Type
					@ no Load	@ full Pressure			Length Depth	Width	Height	Weight (w/oil) lbs.	
AIR	105A	AutoSPLITTER	40 psi to 120 psi	10,000 psi	68	4	1/4	1	10	5	7.75	20	2 Way
	205A	Torque Wrenches AutoSPLITTER Flange Puller	50 cfm @90 psi	10,000 psi	400	50	1.5	2	25.44	16.75	20.5	100	4 Way
	603A	SpinTORQ	150 cipm @100 psi	3,000 psi	10 gpm	4 gpm @1500 psi	6	2.5	21	19	51	205	4 Way
	ST-CU	SpinTORQ Control Unit for use with customer's power unit.							15	8	16	25	4 Way
	610A	Torque Wrenches AutoSPLITTER Flange Puller	150 cfm @100 psi	10,000 psi	550	150	6	2	21	19	51	205	4 Way
ELECTRIC	115E	AutoSPLITTER	110/220 Volts AC Single Ph. 50/60hz	10,000 psi	400	20	.5	2	12.25	12.25	19	64	Dump
	210E	Torque Wrenches AutoSPLITTER	115 Volts A/C	10,000 psi	400	20	.5	1	11.31	7.88	18.56	80	4 Way
	215E	Torque Wrenches AutoSPLITTER Flange Puller	115 Volts A/C	10,000 psi	400	50	1.5	2	12.25	12.25	19.03	95	4 Way
Manual Two Speed	HTP-40H	Stud Tensioners	Hand Powered	40,000 psi	Per Stroke .99 @ 200 psi	Per Stroke .037 @ 40K psi	n/a	60 cu in	22	4.74	9	14	Manual
AIR	HTP 1000	Stud Tensioners	75 cfm @ 100 psi	30,000 psi	36	28	1.5	5	20	20	20	120	Manual
	HTP 2000	Stud Tensioners	75 cfm @ 100 psi	30,000 psi	29	17	1.5	5	20	20	20	130	Manual
Manual Two Speed	150F 150F2	AutoSPLITTER AutoSPREADER	Foot Powered	10,000 psi	Per Stroke .662 @ 325 psi	Per Stroke .16 @ 10K psi	n/a	152 cu in	22.75	3.75	6	26.2	Manual
	150H 150H2	AutoSPLITTER AutoSPREADER	Hand Powered	10,000 psi	Per Stroke .662 @ 325 psi	Per Stroke .16 @ 10K psi	n/a	152 cu in	22.75	3.75	6	26.2	Manual
Manual One Speed	100H 100H2	AutoSPLITTER AutoSPREADER	Hand Powered	10,000 psi	Per Stroke .662 @ 325 psi	Per Stroke .16 @ 10K psi	n/a	55 cu in	23.0	4.75	6	15.8	Manual

Standard Accessories

Models 100H, 105A, 115E, 150H & 150F include 12 ft hydraulic hose and fittings **Models 100H2, 150H2, 150F2** same specs as 100H, 150H & 150F includes pair of 12 ft hydraulic hoses, tee block, load lowering valve & fittings **Models 603A & 610A** include 25 ft hydraulic hose and fittings, 25 ft remote control, filter, regulator, lubricator and liquid filled hydraulic pressure gauge, rugged welded framework protects components - **Model 205A** includes the same, but with 20 ft remote control.

Models 210E and 215E include 25 ft hydraulic hose and fittings, 20 ft remote control cable and liquid filled hydraulic gauge, rugged welded framework protects components **Model HTP1000 & HTP2000** includes liquid filled hydraulic gauge, rugged welded framework protects components, hoses and fittings sold separately **Model HTP2000** includes air-operated suction return pump for fast retraction of stud tensioners **Model HTP-40H** includes 30,000 PSI pressure gauge and fittings.

